

McKinnon Materials, Inc.

5612 56th Commerce Park Blvd.

Tampa FL, 33610

Phone: (813) 622-7031 Fax: (813) 621-9017

Super Vinyl Supreme

<u>Physical Properties</u>		<u>Safety:</u>
<u>Composition:</u>	Solvent based acrylic, used as a sealer on ceramic and acrylic based products such as McKrete.	DANGER! EXTREMELY FLAMMABLE – CONTAINS XYLENE. Keep away from heat sparks and flame. To avoid breathing vapors or spray mist. Open windows and doors or other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air or wear respiratory protection (MOSH/MSHA TC23C or equivalent) or leave the area. Close container after each use and avoid contact with skin.
<u>Color:</u>	Clear	<u>Warranty</u> McKinnon Materials warrants its products to conform to its manufacturing standards. McKinnon Materials will replace or refund the purchase price of non-conforming product at the seller's option; such remedy being exclusive of all others and sole remedy available to the buyer. Buyer hereby expressly waives claim to additional damages. Any claim under this warranty must be made in writing within 7 days of discovery of non-compliance and no later than two years from the date of delivery of product. No representative, distributor or applicator of these products is authorized to modify product, product data or warranty.
<u>Gloss:</u>	Sheen	<u>Important Notice</u> These products are sold subject only to the express warranties contained herein. There are no other warranties by McKinnon Materials of any nature whatsoever expressed or implied. Including any warranties of merchantability or fitness for a particular purpose in connection with this product. Buyer agrees that seller assumes no liability for remote or consequential damages of any kind which result from the use or misuse of the product. Information contained herein is based on data believed to be reliable; however it is the buyer's responsibility to satisfy itself of the product for a particular purpose. Material safety data sheets are available from McKinnon Materials and should be consulted prior to use of the product. This product is intended for use by professionals only. Keep away from children and those not trained in the use of potentially hazardous materials.
<u>Solids by weight:</u>	36%	
<u>Viscosity:</u>	#2 Zahn 21-22 sec	
<u>VOC:</u>	600 grams (5 lbs/GL)	

General Information:

Dry time @ 70 degrees:	Dry to touch approximately 1 hour depending upon temperature in humidity	
Product Advantages:	Resists tire marks Resists mildew	
Application:	Recommend roll on or spray. When applying with a short nap roller (3/8" nap) DO NOT APPLY excessive pressure on the roller, roll with light to medium pressure. Apply vinyl supreme top coat evenly, do not leave puddles or roller marks. Do not apply to areas where standing water is evident.	
Caution: DO NOT apply in temperatures below 50 degrees F to a damp surface or excessively hot surfaces, for example direct sunlight on a hot day, drying may occur too rapidly, causing trapped vapors to bubble. If this occurs, we recommend application during a cooler time of day. Keep away from children. Keep away from direct heat and open flame.		